


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME: LTY40X312CT19 1050mA_3000K	TYPE: YALA ONE	WEIGHT:
SPEC.:	DIM.: 300X1200X12	SERIAL No.:1
MFR.: TECONEX	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 126.00 lm/W			
MODEL	LTY40X312CT19	I _{max} (cd)	1982	S/MH (C0/180)	1.31
NOMINAL POWER (W)	40	LOR (%)	100.0	S/MH (C90/270)	1.34
RATED VOLTAGE (V)	35	TOTAL FLUX (lm)	4630.5	η UP, DN (C0-180)	0.0, 50.0
NOMINAL FLUX (lm)	4630.5	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 50.0
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	35	η down (%)	100.0	CIBSE SHR MAX	1.30

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 10.270m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1937	1956	1970	1956	1937	1956	1970	1956	0- 10	186.3	186.3	4.02, 4.02
20	1904	1936	1973	1936	1904	1936	1973	1936	10- 20	553.2	739.6	16, 16
30	1755	1782	1876	1782	1755	1782	1876	1782	20- 30	869.6	1609	34.8, 34.8
40	1389	1339	1508	1339	1389	1339	1508	1339	30- 40	1029	2638	57, 57
50	815.0	810.2	876.8	810.2	815.0	810.2	876.8	810.2	40- 50	846.8	3485	75.3, 75.3
60	491.7	429.5	401.7	429.5	491.7	429.5	401.7	429.5	50- 60	552.8	4038	87.2, 87.2
70	241.4	257.3	276.6	257.3	241.4	257.3	276.6	257.3	60- 70	328.1	4366	94.3, 94.3
80	126.4	113.0	143.0	113.0	126.4	113.0	143.0	113.0	70- 80	199.2	4565	98.6, 98.6
90	0.4433	0	0	0	0.4433	0	0	0	80- 90	65.26	4631	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 3181.1 lm

%lum = 68.7%

%lamp = 68.7%

Conical surface Flux(120deg): 4038 lm

%lum = 87.2%


%lamp = 87.2%

C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:10.270m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	2483	2512
80	2025	2285
75	2416	2291
70	1963	2244
65	2165	2251
60	2735	2229
55	3415	3132
50	3527	3785
45	4518	4788


C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.97	.94	.96	.93	.91	.92	.90	.89	.87
2.0	.94	.88	.83	.92	.87	.82	.89	.84	.80	.86	.82	.78	.83	.79	.77	.75
3.0	.84	.77	.71	.82	.76	.70	.80	.74	.69	.77	.72	.68	.74	.70	.67	.65
4.0	.75	.68	.61	.74	.67	.61	.72	.65	.60	.70	.64	.59	.67	.63	.59	.57
5.0	.68	.60	.54	.67	.59	.54	.65	.58	.53	.63	.57	.52	.61	.56	.52	.50
6.0	.62	.54	.48	.61	.53	.48	.59	.52	.47	.58	.51	.47	.56	.51	.46	.44
7.0	.57	.48	.43	.56	.48	.42	.54	.47	.42	.53	.47	.42	.52	.46	.42	.40
8.0	.52	.44	.38	.51	.44	.38	.50	.43	.38	.49	.42	.38	.48	.42	.38	.36
9.0	.48	.40	.35	.47	.40	.35	.46	.39	.35	.45	.39	.34	.44	.38	.34	.32
10.0	.44	.37	.32	.44	.37	.32	.43	.36	.32	.42	.36	.31	.41	.35	.31	.30



C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:10.270m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:1	
MFR.: EVERFINE		SUR.:		Shielding Angle:	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.271	.154	.049	.264	.150	.048	.250	.144	.046	.238	.138	.044	.227	.132	.042		
2.0	.257	.141	.043	.250	.138	.043	.239	.133	.041	.229	.128	.040	.219	.124	.039		
3.0	.240	.128	.038	.235	.126	.038	.225	.122	.037	.216	.118	.036	.207	.115	.035		
4.0	.224	.116	.034	.219	.115	.034	.211	.112	.033	.202	.109	.033	.195	.106	.032		
5.0	.209	.107	.031	.205	.105	.031	.197	.103	.030	.190	.100	.030	.183	.098	.029		
6.0	.196	.098	.028	.192	.097	.028	.185	.095	.028	.179	.093	.027	.173	.091	.027		
7.0	.184	.091	.026	.181	.090	.026	.175	.088	.025	.169	.087	.025	.163	.085	.025		
8.0	.173	.085	.024	.170	.084	.024	.165	.082	.023	.159	.081	.023	.155	.079	.023		
9.0	.163	.079	.022	.161	.078	.022	.156	.077	.022	.151	.076	.022	.147	.074	.022		
10.0	.155	.074	.021	.152	.073	.021	.148	.072	.020	.143	.071	.020	.139	.070	.020		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.137	.152	.134	.118	.104	.092	.082	.060	.053	.048	.019	.017	.015	
2.0	.168	.132	.102	.144	.114	.088	.098	.079	.062	.057	.046	.036	.018	.015	.012	
3.0	.159	.114	.079	.136	.098	.068	.093	.068	.048	.054	.040	.028	.017	.013	.009	
4.0	.151	.100	.062	.129	.087	.054	.089	.060	.038	.051	.035	.022	.017	.012	.007	
5.0	.143	.090	.050	.123	.078	.044	.085	.054	.031	.049	.032	.018	.016	.010	.006	
6.0	.136	.081	.042	.117	.070	.036	.081	.049	.026	.047	.029	.015	.015	.009	.005	
7.0	.130	.074	.035	.112	.064	.031	.077	.045	.022	.045	.027	.013	.014	.009	.004	
8.0	.124	.068	.030	.107	.059	.026	.074	.042	.019	.043	.025	.011	.014	.008	.004	
9.0	.118	.063	.026	.102	.055	.023	.071	.039	.016	.041	.023	.010	.013	.007	.003	
10.0	.113	.059	.023	.097	.051	.020	.068	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-06-26

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm										
NAME:					TYPE:			WEIGHT:		
SPEC.:					DIM.:			SERIAL No.:1		
MFR.: EVERFINE					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.9	17.3	16.2	17.5	17.7	15.9	17.3	16.2	17.5	17.7
3H	16.9	18.2	17.2	18.4	18.6	16.8	18.0	17.1	18.3	18.5
4H	17.3	18.5	17.6	18.8	19.0	17.2	18.4	17.5	18.6	18.9
6H	17.7	18.8	18.0	19.1	19.4	17.7	18.8	18.0	19.1	19.3
8H	17.8	18.9	18.2	19.2	19.5	17.8	18.9	18.2	19.2	19.5
12H	17.9	19.0	18.3	19.3	19.6	17.9	19.0	18.3	19.3	19.6
4H 2H	16.2	17.4	16.5	17.7	17.9	16.2	17.4	16.5	17.6	17.8
3H	17.4	18.5	17.8	18.8	19.1	17.3	18.3	17.6	18.6	18.9
4H	18.0	18.9	18.3	19.2	19.6	17.8	18.8	18.2	19.1	19.4
6H	18.5	19.3	18.9	19.7	20.1	18.5	19.3	18.9	19.7	20.0
8H	18.7	19.5	19.1	19.9	20.3	18.7	19.5	19.2	19.9	20.3
12H	18.9	19.6	19.4	20.0	20.4	18.9	19.6	19.3	20.0	20.4
8H 4H	18.2	18.9	18.6	19.3	19.7	18.0	18.8	18.5	19.2	19.6
6H	18.9	19.5	19.3	19.9	20.4	18.8	19.5	19.3	19.9	20.3
8H	19.2	19.8	19.7	20.2	20.7	19.2	19.8	19.7	20.2	20.6
12H	19.5	20.0	20.0	20.5	20.9	19.5	19.9	19.9	20.4	20.9
12H 4H	18.2	18.9	18.6	19.3	19.7	18.1	18.8	18.5	19.2	19.6
6H	18.9	19.5	19.4	19.9	20.4	18.9	19.5	19.4	19.9	20.4
8H	19.3	19.8	19.8	20.3	20.8	19.3	19.8	19.8	20.2	20.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.5				
1.5H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				
2.0H	+ 0.8 / - 1.0					+ 1.0 / - 0.7				

CIE Pub.117, 4631 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 5.3$)

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-06-26

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	65	54	48	64	54	48	63	54	48	42
0.80	75	64	58	74	64	58	72	63	57	51
1.00	82	73	67	81	72	66	79	73	66	60
1.25	89	80	74	88	79	74	85	78	73	66
1.50	93	85	79	92	84	79	89	82	78	71
2.00	99	92	86	97	91	86	94	89	84	77
2.50	102	96	91	100	94	90	97	92	88	80
3.00	105	99	95	103	98	94	99	95	91	83
4.00	108	104	100	106	102	98	102	99	96	87
5.00	110	106	103	108	104	101	104	101	98	89
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 10.270m [K=1.0000]
Remarks:

AAI Figure

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity: 65.0%
 Test Distance: 10.270m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature:25.3DEG
Operators:DAMIN
Test Date:2021-06-26

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:35.000V I:1.0500A P:36.750W PF:1.0000 Freq:0Hz Lamp Flux:4630.5x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1970
L_0~180 (75) av	2273
L_0~180 (85) av	2096
L_90~270 (65) av	2188
L_90~270 (75) av	2170
L_90~270 (85) av	1979
L_45 (65) av	2173
L_45 (75) av	1864
L_45 (85) av	1708

Standard: GB/T 29293-2012

C Range: 0 - 90DEG
 C Interval: 5.0DEG
 Test Speed: MEDIUM
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
 Humidity:65.0%
 Test Distance:10.270m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 90DEG
C Interval: 5.0DEG
Test Speed: MEDIUM
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2021-06-26

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity: 65.0%
Test Distance: 10.270m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.295
Humidity:65.0%
Test Distance:10.270m [K=1.0000]
Remarks:

```